Numatic H-Class Range

HZ390L/S (H Class)



| Data Sheet | |
|-------------------------------------|---------------------------------------|
| Rated Motor Power (W) | 960 W |
| Power | 230v AC 50/60Hz |
| Airflow Motor only | 48 L/sec |
| Max Suction H ² 0 | 2500 |
| Kit | AA18 |
| Capacity (DRY) | 18.0 Litres |
| Cleaning Range (M) | 26.8 |
| Weight (Ready to use) | 11.2 / 12.6 kg |
| Dimensions (W x L x H) Long Handle | 400mm x 450mm x 1010mm |
| Dimensions (W x L x H) Short Handle | 400mm x 450mm x 600mm |
| Mains Lead | HO5VV-F 10 x 3 x 1.00 mm ² |
| Protection Class | Class I |
| Dust Bag | NVM-2BH |
| Dust Hazard Class | Н |
| Filtration Efficiency Class | H13 (EN1822) |

H-Class equipment is the legal requirement when working with high-risk, non-explosive, hazardous dusts and materials, including asbestos.

The HZ390 is engineered to meet this demanding standard, so you can breathe easy.

H-Class Compliant

Compact & Ready

Take Control

High Efficiency

Powerful & Professional

All-Terrain

UNITED KINGDOM: www.numatic.co.uk **NETHERLANDS:** www.numatic.nl PORTUGAL: www.numatic.pt

GERMANY: www.numatic.de SWITZERLAND: www.numatic.ch

SPAIN: www.numatic.es

FRANCE: www.numatic.fr SOUTH AFRICA: www.numatic.co.za

Specification subject to change without prior notice www.numatic.co.uk © Numatic International Limited



