## **Numatic** H-Class Range

## HZ900 HZD900 (H Class)



rtified Paras ration	
	C C C C C C C C C C C C C C C C C C C

	F
	Α
CLASS	Ν
	k
	C
	C
	۷
	E
<b>MA</b>	Ν
$\square$	F
	E

Data Sheet		
Rated Motor Power (W)	960 W / 960 W x 2	
Power	230v AC 50/60Hz	
Airflow Motor only	48 / 96 L/sec	
Max Suction H <sup>2</sup> 0	2500	
Kit	AA20 / BB20	
Capacity (DRY)	40.0 Litres	
Cleaning Range (M)	26.8	
Weight (Ready to use)	28.0 / 30.0 kg	
Dimensions (W x L x H) Long Handle	490mm x 800mm x 880mm	
Mains Lead	HO5VV-F 10 x 3 x 1.00 mm <sup>2</sup>	
Protection Class	Class I	
Dust Hazard Class	Н	
Filtration Efficiency Class	H13 (EN1822)	

In the selection of any dust control machine, it is vitally important that the size, power and capacity are given serious consideration from the outset, as the right choice will play an important and on-going part in terms of user satisfaction. The 900 series provides a choice of Simplex one motor or Duplex two motor models

**Advanced** Filtration **Built** to Last **Powerful** & Efficient **Clean** for Longer Easy Clean & Safe Emptying



UNITED KINGDOM: www.numatic.co.uk GERMANY: www.numatic.de NETHERLANDS: www.numatic.nl PORTUGAL: www.numatic.pt

SWITZERLAND: www.numatic.ch SOUTH AFRICA: www.numatic.co.za SPAIN: www.numatic.es

FRANCE: www.numatic.fr

Specification subject to change without prior notice www.numatic.co.uk © Numatic International Limited

